



Vanadium 



→ FEROVAN[®]

AMG VANADIUM ADVANTAGE

AMG Vanadium's low-aluminum ferrovanadium is known as FEROVAN[®]. This precision-engineered product offers distinct advantages to steelmakers, including maximum recoveries and a range of other benefits.

FEROVAN[®], the most effective vanadium additive for killed and semi-killed steels and alloyed cast irons, is ideal for a broad range of applications including structural steel, HSLA steel, reinforcing bar, line pipe and rail steel. It can be used for primary melting in electric arc, induction and basic oxygen furnaces and secondary refining in vacuum degassers and LMF stations.

A variety of packaging options are available at our Cambridge, Ohio facility to meet your specific packaging requirements.

METGREEN[®]

AMG Vanadium
Environmental Responsibility



- **Quality** – FEROVAN® is produced under the strict quality assurance programs of our technical department and is managed by extensive use of process control charts to meet the most exacting demands of today's steel producers and consumers.
- **FEROVAN® is ISO 9001:2008 certified.**
- **Oxidation Protection** – FEROVAN® is engineered with a dilute vanadium content and contains Si to protect the V from oxidation.
- **Low Melting Point** – with a 2675° F (1468° C) liquidus, FEROVAN® is the lowest-melting-point FeV commercially available, resulting in maximum solubility and the highest consistent recoveries.
- **High Density** – FEROVAN®'s density of 6.4 g/cc (90% of liquid steel's density) ensures good melt penetration which minimizes alloy flotation and front-to-back ladle analysis variations.
- **Low Carbon Content** – FEROVAN®'s 50:1 vanadium : carbon ratio permits use on the lowest-carbon steels to the highest-carbon steels, without requiring additional carbon removal by the steelmaker.
- Perfect for EAF steel since the vanadium readily combines with existing nitrogen without increasing nitrogen or carbon content.
- **Low Aluminum Content** – FEROVAN®'s controlled, low-aluminum content offers maximum castability and minimizes nozzle blockages.
- **Application/Versatility** – FEROVAN® is the most effective vanadium additive for killed and semi-killed steels and alloyed cast irons. It is ideal for a broad range of applications: structural steel, HSLA steel, reinforcing bar, line pipe and rail steel. It is also suitable for primary melting in electric arc, induction and basic oxygen furnaces, and secondary refining in vacuum degassers and LMF stations.
- **Custom Packaging** – FEROVAN® is packaged to meet customers' requirements on heat weights, vanadium aims and material handling. FEROVAN® is available in sealed bags, cans, drums and supersacks. Please contact us about your specific packaging requirements.
- **No Hydrogen Pickup** – FEROVAN®, in its solid alloy form, does not absorb or retain water or hydrogen as do porous, nonmelted vanadium additives.

CHEMISTRY

V	50-60%	
Al	0.10%	Maximum
Si	12.00%	Maximum
C	1.00%	Maximum
Size	2 inches & down	

NOTE: Please direct product and commercial questions to Jim Carter.

Phone: 1-740-435-4641
 1-800-762-2323 x4641
 Fax: 740-432-5937
 Email: jcarter@amg-v.com
 Mobile: 614-804-0731



Phone: 1-800-318-8662 or
 1-740-435-4600
 Fax: 740-432-5937
www.amg-v.com

We are a proud member of the AMG group of companies – a global leader in materials for advanced industrial applications.